

PRODUCT DATA SHEET

OXYvisor Optical Oxygen Analyzer

Rugged oxygen (O₂) analyzer for either parts per million (ppm) or percent level measurements in natural gas

Operators of natural gas processing plants and pipelines must maintain the quality of natural gas to protect mechanical infrastructure, to ensure reliable gas processing, and to deliver gas that meets end user specifications. O₂ in natural gas can promote corrosive acid formation, reduce the efficiency of the amine sweetening process, or create an explosive atmosphere. Any leak in production manifolds, compressor seals, pumps or process equipment allows O₂ to enter the natural gas stream, resulting in unplanned downtime, reduced process efficiency or a safety concern.

The OXYvisor utilizes optical quenched luminescence technology to measure the O₂ concentration in natural gas. Light from a light emitting diode (LED) is transmitted through a fiber-optic cable to the O₂ sensing luminophore at the sensor tip. In the presence of O₂, the resulting fluorescence is quenched at a rate proportional to the O₂ concentration.

Reliable measurement

The luminophore is unaffected by contaminants or flow rate. The OXYvisor has no cross-sensitivity to common contaminants in natural gas, including carbon dioxide (CO₂) and hydrogen sulfide (H₂S), and will deliver an accurate O₂ measurement every time.

User simplicity

OXYvisor features through-the-glass programming via an infrared keypad. Users can easily access the intuitive configuration and calibration menus in a hazardous area without the need for a hot work permit, saving time and minimizing additional risk planning procedures. The optical O₂ sensor is connected via a separate junction box, simplifying field sensor replacement while eliminating any exposure of the electronics to dust and humidity.

Remote operation

OXYvisor allows users to transmit data, initiate automatic calibration, or configure the software remotely via Modbus RS485. The built-in data logger stores calibration history and error messages, providing users with analyzer performance history.



KEY BENEFITS

- Rugged IP66, NEMA 4X enclosure
- Certified for hazardous areas: IEC & ATEX (Zone 1 & Zone 2) and cULus (Class I, Div 2 & Class I Zone 1)
- Local display HMI with through-the-glass programming
- Manual & auto-calibration capable
- Pressure compensation
- Modbus RS485 RTU serial communication
- USB data trend storage
- Field replaceable O₂ sensor
- Sensor immune to H₂S, CO₂, SO₂ & H₂ up to percent levels

APPLICATIONS

- Pipeline quality and custody transfer
- Inlet feed to gas plant
- Wellhead piping leading to production manifold
- Inlet and outlet on the amine absorber
- Blanket gas on amine storage tank
- Biomethane production

KEY MARKETS

NATURAL GAS

- Production manifolds
- Processing plants
- Underground storage sites
- Gathering lines
- Custody transfer
- Transmission pipelines

PERFORMANCE SPECIFICATIONS

Technology	Quench luminescence technology
Range*	BOS1: 0-4.2% O ₂ BOS2: 0-100% O ₂ BOS3: 0-300 parts per million by volume (ppmv) with over-range of 1000 ppmv
Accuracy*	BOS1: ±0.002% O ₂ or ±3% of the measured value, whichever is greater BOS2: ±0.4% O ₂ at 20.9% O ₂ , ±0.05% O ₂ at 0.2% O ₂ BOS3: ±2 ppm or ±5% of measured value, whichever is greater
Resolution*	BOS1: ±0.0007% O ₂ at 0.002% O ₂ , ±0.0015% O ₂ at 0.02% O ₂ BOS2: ±0.01% O ₂ at 0.21% O ₂ , ±0.1% O ₂ at 20.9% O ₂ BOS3: 10 ±0.5 ppm; 100 ±0.8 ppm; 200 ±1.5 ppm
Limit of detection*	BOS1: 0.002% O ₂ BOS2: 0.03% O ₂ BOS3: 0.5 ppm O ₂
Response time (T₉₀)*	BOS1: <6 sec. BOS2: <6 sec. BOS3: <3 sec. based on 0-300 ppm measurement range
User interface	Liquid crystal display with (four) proximity switches, infrared contacts for interactive user interface at HMI
Inputs	Sensor inputs Optical O ₂ : (one) O ₂ optical input BOS1, BOS2 or BOS3 sensor (SMA connector) RTD: temp (one) Pt1000 4-wire RTD Inputs (isolated) Analog input: (one) 4-20 mA input (24 VDC active from OXYvisor) – user-configurable for temperature or pressure transmitter Pressure sensor: (one) onboard integrated pressure sensor measures and compensates for ambient pressure conditions Digital inputs (Two) optically isolated inputs 5 VDC powered, remote initiation of automatic calibration and live validation gas
Outputs	(Two) programmable current outputs with galvanic isolation, 4-20 mA (active), linear or bi-linear (Four) programmable relays, optically isolated, 24 VDC @ 0.05A pilot duty, 24 VDC @ 0.4A resistive load (One) Modbus RTU serial protocol RS485
Power	AC four-wire version: 85-264 VAC, 47-63 Hz, 6W DC four-wire version: 21.6-26.4 VDC, 5W
Operating temperature	OXYvisor: -20 to +55°C (-4 to 131°F) BOS1, BOS2, BOS3: 0 to 50°C (32 to 122°F)
Physical dimensions (W x H x D)	140 x 305 x 290 mm (5.5 x 12.0 x 11.0 in.)
Weight	6.2 kg (13.7 lb)
Environmental rating	IEC Installation Category II Pollution Degree 2 Maximum altitude: 2,000 meters (6,561 ft) Ingress rating: IP66 and NEMA 4X
Approvals and certifications	ATEX and IECEx: II 2 G Ex db op is IIC T4 Gb Class I Zone 1 AEx db op is IIC T4 Gb Class I Zone 1 Ex db op is IIC T4 Gb ATEX and IECEx: Ex ec [ic] op is IIC T4 Gc Class I Zone 2 AEx ec [ic] op is IIC T4 Gc Class I Zone 2 Ex ec [ic] op is IIC T4 Gc Class I Division 2 Group A, B, C, D T4a CE Compliance: Complies with all relevant European Directives

*Sensor dependent

SALES, SERVICE & MANUFACTURING

USA - Pennsylvania

150 Freeport Road
Pittsburgh PA 15238
Tel: +1 412 828 9040
Fax: +1 412 826 0399

USA - Delaware

455 Corporate Blvd.
Newark DE 19702
Tel: +1 302 456 4400
Fax: +1 302 456 4444

Canada - Alberta

2876 Sunridge Way NE
Calgary AB T1Y 7H9
Tel: +1 403 235 8400
Fax: +1 403 248 3550

WORLDWIDE SALES AND SERVICE LOCATIONS

USA

Tel: +1 713 466 4900
Fax: +1 713 849 1924

Brazil

Tel: +55 19 2107 4100

France

Tel: +33 1 30 68 89 20
Fax: +33 1 30 68 89 99

Germany

Tel: +49 2159 9136 0
Fax: +49 2159 9136 39

India

Tel: +91 80 6782 3200
Fax: +91 80 6780 3232

Singapore

Tel: +65 6484 2388
Fax: +65 6481 6588

China

Beijing
Tel: +86 10 8526 2111
Fax: +86 10 8526 2141
Chengdu
Tel: +86 28 8675 8111
Fax: +86 28 8675 8141
Shanghai
Tel: +86 21 5868 5111
Fax: +86 21 5866 0969



© 2019, by AMETEK, Inc. All rights reserved. Printed in the F-0552 Rev 1 (1119)
One of a family of innovative process analyzer solutions from AMETEK Process Instruments.
Specifications subject to change without notice.

